

welding machines from Woltersdorf

MIG 400 E

MIG/MAG- welding machine
Synergic control - remote control



thyristor controlled; stepless; a machine of the newest generation
electronic control of all welding parameters
adjustment at the wire feeder WF41C
remote control

Technical data

Power source MIG 400 E

Mains Voltage:

Welding output:

Ratings:

Parameter adjustment:

V/A-digital instruments:

Liquid cooling:

Protection:

Weight:

Dimensions:

Wire feeder unit WF 41 CP

MIG 400 E (article no. 05400-E)

3 x -400 V / 50 Hz

40 - 400 A

400 A / 60% ED (A)

300 A / 100% ED (A)

stepless – remote control

standard

yes

IP 23, S

150 kg

950 x 360(485) x 950 mm power source

geared powerful 4- rolls wire drive system

Electronic controlled wire ranning

Soft start control

Burn back control

2- and 4- stroke- torch triggering

wire 0,8 - 1,6 mm for Normal-MIG/MAG

wire 0,9 - 1,2 mm for inner shield wire

remote control and potentiometer for adjustment

Weight: 15 kg

Dimensions: 550 x 230 x 450 mm

length 1-30 m

Interconnection cable package:

producer:

WOLTERS DORF Schweißmaschinen GmbH, Eichendamm 3, D-15569 Woltersdorf

Tel.: 0049 (0) 3362/5398, Fax: 0049 (0) 3362/75307

www.woltersdorf-schweiss.de